

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2004-291855

(43)Date of publication of application : 21.10.2004

(51)Int. Cl.

B60C 5/00

B60B 19/00

(21)Application number : 2003-088287 (71)Applicant : HONDA MOTOR CO LTD


(22)Date of filing : 27.03.2003 (72)Inventor : KASHIWAI MIKIO
IIIZUMI TORU
KAMIYAMA YOICHI
TAKAGI HISAMITSU
HOSOKAWA TOSHIYUKI

(54) NOISE REDUCTION STRUCTURE OF TIRE

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a noise reduction structure of tire capable of preventing an air column resonance in a pneumatic chamber of the tire, extending the service life of noise reduction member and further performing an easy adjustment of a wheel balance.

SOLUTION: A resilient noise reduction member having a longer length than the maximum circumferential length of an outer circumferential inner wall surface 15 is compressed and arranged in such a way that the resilient noise reduction member is contacted with the outer circumferential inner wall surface 15 along a circumferential direction of the outer circumferential inner wall surface 15 of an air chamber 13 of a pneumatic tire 12.



LEGAL STATUS

[Date of request for examination] 27.01.2004

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's
decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office